

Site Address

Roofbuddy quote ID

Works match Roofbuddy quote specifications

Works match - Comments

Roofing Sheets

Roofing Sheets - General

- | | |
|--|--|
| <input type="checkbox"/> Overhang 50mm to gutter | <input type="checkbox"/> Paper tensioned at 20mm to gutter |
| <input type="checkbox"/> Purlin spacing 900mm | <input type="checkbox"/> Stop ends folded |
| <input type="checkbox"/> No holes or gaps | <input type="checkbox"/> Turn downs for low pitch |

Comments

Roofing Sheets - Aesthetic

- | | |
|---|--|
| <input type="checkbox"/> Laid square at right angles | <input type="checkbox"/> Tidy and straight |
| <input type="checkbox"/> Dents and scratches within tolerance | <input type="checkbox"/> Laps correct (no kick-outs) |
| <input type="checkbox"/> Correct touch up paint applied | |

Comments

Roofing Sheets - Fixings

- | | |
|--|--|
| <input type="checkbox"/> Correct screw / rivet pattern | <input type="checkbox"/> Over/Under screw within tolerance |
| <input type="checkbox"/> Nothing punching through timber | <input type="checkbox"/> Purlin strips for clear sheets |
| <input type="checkbox"/> Mesh under 4 degrees | <input type="checkbox"/> Drip edge under 4 degrees |

Comments

Roofing sheets - Commercial

- | | |
|--|---|
| <input type="checkbox"/> Mesh compliant | <input type="checkbox"/> Expansion fixings on long sheets |
| <input type="checkbox"/> Neo's and washers over 8m | <input type="checkbox"/> Purlin spacing 1500mm |
| <input type="checkbox"/> Profile compliant | |

Comments

Flashings

Flashings - General

- | | |
|--|--|
| <input type="checkbox"/> Dents and scratches | <input type="checkbox"/> Detailing |
| <input type="checkbox"/> Correct screw / rivet pattern | <input type="checkbox"/> Over/Under screw within tolerance |
| <input type="checkbox"/> Soft edge pushed down | <input type="checkbox"/> Cut in correctly |

Comments

Flashings - Ridges

- | | |
|---|-----------------------------------|
| <input type="checkbox"/> Connecting junctions | <input type="checkbox"/> Hip ends |
| <input type="checkbox"/> High wind zone compliant | |

Comments

Flashings - Aprons, barges and headcaps

- | | |
|--|--|
| <input type="checkbox"/> Diverters at ends | <input type="checkbox"/> Tucked under weatherboard |
| <input type="checkbox"/> Z flashings installed | |

Comments

Flashings - Valleys

- | | |
|--|--|
| <input type="checkbox"/> 50mm run into gutter | <input type="checkbox"/> Straight cut lines |
| <input type="checkbox"/> Tray dimensions compliant | <input type="checkbox"/> Junctions compliant |

Comments

Flashings - Pitch change

- | | |
|---|---|
| <input type="checkbox"/> Angle correct | <input type="checkbox"/> Junctions robust and compliant |
| <input type="checkbox"/> Angle correct - Junctions robust and compliant | |

Comments

Flashings - Parapet

- | | |
|---|---|
| <input type="checkbox"/> Under saddle if required | <input type="checkbox"/> Expansion join if required |
|---|---|

Comments

Penetrations

Penetrations - General

- | | |
|---|--|
| <input type="checkbox"/> Dektite size, location and orientation | <input type="checkbox"/> Areal and dishes removed and replaced |
|---|--|

Comments

Penetrations - Chimneys and skylights

- | | |
|---|--|
| <input type="checkbox"/> Chase & associated flashings | <input type="checkbox"/> MS used |
| <input type="checkbox"/> Cricket flashings / diverter flashings | <input type="checkbox"/> Flashing kits & cut ins |
| <input type="checkbox"/> No penetrations into kit | <input type="checkbox"/> No sheets kicking up |

Comments

Penetrations - Back-trays

- | | |
|--|--|
| <input type="checkbox"/> Correct width and length | <input type="checkbox"/> Matching each-other |
| <input type="checkbox"/> On all penetrations over 80mm | <input type="checkbox"/> On short barges |
| <input type="checkbox"/> On barge junctions | <input type="checkbox"/> On lap penetrations |

Comments

Penetrations - Fixings

- | | |
|--|--|
| <input type="checkbox"/> Correct screw / rivet pattern | <input type="checkbox"/> Over/Under screw within tolerance |
| <input type="checkbox"/> 50mm rivet spacing on Dektite's | <input type="checkbox"/> MS on chase flashings |
| <input type="checkbox"/> Washers and silicon on joins | |

Comments

Gutters

Gutters - General

- | | |
|---|---|
| <input type="checkbox"/> Sufficient fall | <input type="checkbox"/> Bracket spacings compliant |
| <input type="checkbox"/> Mitres compliant | |

Comments

Gutters - Aesthetic

- | | |
|--|---|
| <input type="checkbox"/> Tidy and straight | <input type="checkbox"/> Dents and scratches within tolerance |
| <input type="checkbox"/> Tidy joins | <input type="checkbox"/> Droppers square and level |
| <input type="checkbox"/> Dropper penetration clean cut | |

Comments

Gutters - Fixings and Junctions

- | | |
|--|---|
| <input type="checkbox"/> Correct screw / rivet pattern | <input type="checkbox"/> Over-sealed and under-sealed |
|--|---|

Comments

General notes and feedback

Overall Comments

QA signed off

- | | |
|------------------------------|-----------------------------|
| <input type="checkbox"/> Yes | <input type="checkbox"/> No |
|------------------------------|-----------------------------|